

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/820,570	04/08/2004	Michael L. Boroson	87454RLO 8580	
7590 05/27/2005		EXAMINER		
Pamela R. Crocker			DONG, DALEI	
Eastman Kodak Company 343 State Street			ART UNIT	PAPER NUMBER
Rochester, NY 14650-2201			2879	
		DATE MAILED: 05/27/2005		

Please find below and/or attached an Office communication concerning this application or proceeding.

		E				
•	Application No.	Applicant(s)				
Office Action Summer	10/820,570	BOROSON ET AL.				
Office Action Summary	Examiner	Art Unit				
	Dalei Dong	2879				
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet with the	correspondence address				
A SHORTENED STATUTORY PERIOD FOR REPL' THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a reply If NO period for reply is specified above, the maximum statutory period of Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	36(a). In no event, however, may a reply be ti y within the statutory minimum of thirty (30) da will apply and will expire SIX (6) MONTHS fron , cause the application to become ABANDONE	mely filed ys will be considered timely. n the mailing date of this communication. ED (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on <u>08 A</u>	pril 2004.					
	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims						
4) Claim(s) 1-31 is/are pending in the application. 4a) Of the above claim(s) is/are withdray. 5) Claim(s) is/are allowed. 6) Claim(s) 1-31 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/o	wn from consideration.					
Application Papers						
9) ☐ The specification is objected to by the Examine 10) ☐ The drawing(s) filed on 08 April 2004 is/are: a) Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the Ex	☑ accepted or b)☐ objected to drawing(s) be held in abeyance. Se ion is required if the drawing(s) is ob	ne 37 CFR 1.85(a). Djected to. See 37 CFR 1.121(d).				
Priority under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority document: 2. Certified copies of the priority document: 3. Copies of the certified copies of the priority application from the International Bureau * See the attached detailed Office action for a list	s have been received. s have been received in Applicat rity documents have been receiv u (PCT Rule 17.2(a)).	ion No ed in this National Stage				
Attachment(s)						
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	4) Interview Summary Paper No(s)/Mail D					
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date 4/8/2004.		Patent Application (PTO-152)				

Application/Control Number: 10/820,570

Art Unit: 2879

DETAILED ACTION

Specification

1. The disclosure is objected to because of the following informalities:

On Page 1, first paragraph of the Disclosure, Applicant fails to fill in the Serial number of the U.S. Patent Application in which the present patent application is cross-referenced to.

Appropriate correction is required.

Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 1-4, 6-8, 10-19, 21-23 and 25-31 are rejected under 35 U.S.C. 103(a) as being unpatentable over Applicant's Admitted prior art in view of U.S. Patent No. 6,873,093 to Yu.

Regarding to claim 1, Applicant's admitted prior art in Figure 1 of the Disclosure, discloses a tuned OLED device (10), comprising a microcavity structure (70) including a light-emitting layer (50) for producing light, a semitransparent reflector (30), and a reflector layer (90) disposed on opposite sides of the light-emitting layer (50), the

microcavity structure enhancing on-axis (125) light produced from the light-emitting layer in at least one particular wavelength to produce a desired on-axis (125) viewed color while not substantially enhancing on-axis (125) other wavelength of such light.

However, Applicant's admitted prior art does not disclose a layer including a color change medium which is responsive to wavelengths of light shorter than the particular wavelength by absorbing such shorter wavelengths of light and emitting light corresponding in color to the particular wavelength, thereby improving the color of the light produced by the OLED device when viewed in an off-axis direction.

The Yu reference teaches in Figures 5 and 6, an organic light-emitting diode display structure including: a layer (365) including a color change medium (312, 317, 322) which is responsive to wavelengths of light shorter (blue light with shorter wavelength) than the particular wavelength (green light wavelength and red light wavelength) by absorbing such shorter wavelengths of light (blue) and emitting light corresponding in color (green and red) to the particular wavelength (green light wavelength and red light wavelength) for the purpose of improving contrast ratios between different colors and thus improves the readability of the OLED device in high ambient light conditions.

Thus, it would have been obvious to one having ordinary skill in the art at the time the invention was made to have utilize the color changing layer of Yu for the OLED device of Applicant's admitted prior art in order to improving contrast ratios between different colors and thus improves the readability of the OLED device in high ambient light conditions.

Regarding to claim 2, Applicant's admitted prior art in Figure 1, discloses the light-emitting layer (50) produces broadband wavelength light.

Regarding to claim 3, Applicant's admitted prior art in Figure 1, discloses the particular wavelength of on-axis light is in the red, green, or blue portion of the spectrum.

Regarding to claim 4, Yu teaches in Figures 5 and 6, the color change medium layer (365) is disposed over the semitransparent reflector (224, where the Examiner interprets anode 224 as the semitransparent reflector layer of the OLED of the Yu reference) and the motivation to combine is the same as above.

Regarding to claim 6, Applicant's admitted prior art in Figure 1, discloses the reflector (90) also functions as an electrode.

Regarding to claim 7, Applicant's admitted prior art in Figure 1, discloses the semitransparent reflector (30) also functions as an electrode.

Regarding to claim 8, Yu teaches in Figures 5 and 6, the device is in a passive matrix device and the motivation to combine is the same as above.

Regarding to claim 10, Applicant's admitted prior art in Figure 1, discloses the microcavity structure (70) further includes a transparent cavity-spacer layer (35).

Application/Control Number: 10/820,570

Art Unit: 2879

Regarding to claim 11, Applicant's admitted prior art in Figure 1, discloses the thickness of the transparent cavity-spacer layer (35), refractive index of the transparent cavity-spacer layer (35), or both, are adjusted in conjunction with the thickness and refractive index of the layers of the tuned OLED device to tune the microcavity structure to the desired color.

Regarding to claim 12, Applicant's admitted prior art in Figure 1, discloses the device (10) is bottom-emitting.

Regarding to claim 13, Applicant's admitted prior art in Figure 1, discloses it is old and well known in the art to have the device (10) is top-emitting.

Regarding to claim 14, Yu teaches in Figures 5 and 6, the OLED device including a color filter (370) and the motivation to combine is the same as above.

Regarding to claim 15, Applicant's admitted prior art in Figure 1 of the Disclosure, discloses a tuned OLED device (10), comprising a microcavity structure (70) including a light-emitting layer (50) for producing light, a semitransparent reflector (30), and a reflector layer (90) disposed on opposite sides of the light-emitting layer (50), the microcavity structure enhancing on-axis (125) light produced from the light-emitting layer in at least one particular wavelength to produce a desired on-axis (125) viewed color while not substantially enhancing on-axis (125) other wavelength of such light.

However, Applicant's admitted prior art does not disclose an array of different color pixels wherein at least two different color pixels having a layer including a color change medium which is responsive to wavelengths of light shorter than the particular wavelength by absorbing such shorter wavelengths of light and emitting light corresponding in color to the particular wavelength, thereby improving the color of the light produced by the OLED device when viewed in an off-axis direction.

The Yu reference teaches in Figures 5 and 6, an organic light-emitting diode display structure having an array of different color pixels having: a layer (365) including a color change medium (312, 317, 322) which is responsive to wavelengths of light shorter (blue light with shorter wavelength) than the particular wavelength (green light wavelength and red light wavelength) by absorbing such shorter wavelengths of light (blue) and emitting light corresponding in color (green and red) to the particular wavelength (green light wavelength and red light wavelength) for the purpose of improving contrast ratios between different colors and thus improves the readability of the OLED device in high ambient light conditions.

Thus, it would have been obvious to one having ordinary skill in the art at the time the invention was made to have utilize the color changing layer of Yu for the OLED device of Applicant's admitted prior art in order to improving contrast ratios between different colors and thus improves the readability of the OLED device in high ambient light conditions.

Regarding to claim 16, Yu teaches in Figures 5 and 6, there is a common lightemitting layer (emitting the same color blue for all three pixels) for the microcavity

Page 7

structure for each of the at least two such different color pixels.

Regarding to claim 17, Applicant's admitted prior art in Figure 1, discloses the

light-emitting layer (50) produces broadband wavelength light.

Regarding to claim 18, Applicant's admitted prior art in Figure 1, discloses the

particular wavelength of on-axis light is in the red, green, or blue portion of the spectrum.

Regarding to claim 19, Yu teaches in Figures 5 and 6, the color change medium

layer (365) is disposed over the semitransparent reflector (224, where the Examiner

interprets anode 224 as the semitransparent reflector layer of the OLED of the Yu

reference) and the motivation to combine is the same as above.

Regarding to claim 21, Applicant's admitted prior art in Figure 1, discloses the

reflector (90) also functions as an electrode.

Regarding to claim 22, Applicant's admitted prior art in Figure 1, discloses the

semitransparent reflector (30) also functions as an electrode.

Regarding to claim 23, Yu teaches in Figures 5 and 6, the device is in a passive matrix device and the motivation to combine is the same as above.

Regarding to claim 25, Applicant's admitted prior art in Figure 1, discloses the microcavity structure (70) further includes a transparent cavity-spacer layer (35).

Regarding to claim 26, Applicant's admitted prior art in Figure 1, discloses the thickness of the transparent cavity-spacer layer (35), refractive index of the transparent cavity-spacer layer (35), or both, are adjusted in conjunction with the thickness and refractive index of the layers of the tuned OLED device to tune the microcavity structure to the desired color.

Regarding to claim 27, Yu teaches in Figures 5 and 6, one or more of the OLED (205) layers are separately patterned for one or more of the pixels and the motivation to combine is the same as above.

Regarding to claim 28, Applicant's admitted prior art in Figure 1, discloses the device (10) is bottom-emitting.

Regarding to claim 29, Applicant's admitted prior art in Figure 1, discloses it is old and well known in the art to have the device (10) is top-emitting.

Regarding to claim 30, Yu teaches in Figures 5 and 6, the OLED device including one or more of the pixels further include different color filters (370) and the motivation to combine is the same as above.

Regarding to claim 31, Yu teaches in Figures 5 and 6, the device is a full color device (comprises of red, green and blue colors).

4. Claims 5 and 20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Applicant's Admitted prior art in view of U.S. Patent No. 6,873,093 to Yu and in further view of U.S. Patent No. 6,309,486 to Kawaguchi.

Regarding to claim 5, Applicant's admitted prior art in view of the Yu reference discloses a tuned OLED device (10); comprising a microcavity structure (70) including a light-emitting layer (50) for producing light, a semitransparent reflector (30), and a reflector layer (90) disposed on opposite sides of the light-emitting layer (50), the microcavity structure enhancing on-axis (125) light produced from the light-emitting layer in at least one particular wavelength to produce a desired on-axis (125) viewed color while not substantially enhancing on-axis (125) other wavelength of such light; and a layer including a color change medium which is responsive to wavelengths of light shorter than the particular wavelength by absorbing such shorter wavelengths of light and emitting light corresponding in color to the particular wavelength, thereby improving the color of the light produced by the OLED device when viewed in an off-axis direction.

Application/Control Number: 10/820,570

Art Unit: 2879

However, Applicant's admitted prior and the Yu reference does not disclose a dielectric stack disposed between the color changing medium layer and the semitransparent reflector.

The Kawaguchi reference teaches in Figure 3, an organic light-emitting device having a dielectric stack (2 and/or 3) disposed between the color changing medium layer (4, 5 and 6) and the semitransparent reflector (8) for the purpose of providing a flat surface without adversely affecting the color conversion characteristics of the color changing medium layer and further blocks impurities entered into the device and thus prevent the degradation of the color changing medium layer.

Thus, it would have been obvious to one having ordinary skill in the art at the time the invention was made to have utilize the color changing layer of Yu and the dielectric stack of Kawaguchi for the OLED device of Applicant's admitted prior art in order to improving contrast ratios between different colors and thus improves the readability of the OLED device in high ambient light conditions and providing a flat surface without adversely affecting the color conversion characteristics of the color changing medium layer and furthermore blocks impurities entered into the device and thus prevent the degradation of the color changing medium layer.

Regarding to claim 20, Kawaguchi reference teaches in Figure 3, an organic lightemitting device having a dielectric stack (2 and/or 3) disposed between the color changing medium layer (4, 5 and 6) and the semitransparent reflector (8) and the motivation to combine is the same as above.

5. Claims 9 and 24 are rejected under 35 U.S.C. 103(a) as being unpatentable over Applicant's Admitted prior art in view of U.S. Patent No. 6,873,093 to Yu and in further view of U.S. Patent No. 6,281,634 to Yokoyama.

Regarding to claim 9, Applicant's admitted prior art in view of the Yu reference discloses a tuned OLED device (10), comprising a microcavity structure (70) including a light-emitting layer (50) for producing light, a semitransparent reflector (30), and a reflector layer (90) disposed on opposite sides of the light-emitting layer (50), the microcavity structure enhancing on-axis (125) light produced from the light-emitting layer in at least one particular wavelength to produce a desired on-axis (125) viewed color while not substantially enhancing on-axis (125) other wavelength of such light; and a layer including a color change medium which is responsive to wavelengths of light shorter than the particular wavelength by absorbing such shorter wavelengths of light and emitting light corresponding in color to the particular wavelength, thereby improving the color of the light produced by the OLED device when viewed in an off-axis direction.

However, Applicant's admitted prior and the Yu reference does not disclose the device is an active matrix device.

The Yokoyama reference teaches in Figures 5 and 8, the color electroluminescent display device is an active matrix device for the purpose of actively address each pixel within the display device.

Thus, it would have been obvious to one having ordinary skill in the art at the time the invention was made to have utilize the color changing layer of Yu and active OLED device of Yokoyama for the OLED device of Applicant's admitted prior art in

order to improving contrast ratios between different colors and thus improves the readability of the OLED device in high ambient light conditions and providing a flat surface without adversely affecting the color conversion characteristics of the color changing medium layer and furthermore actively address each pixel of the display device to obtain desired color.

Regarding to claim 24, Yokoyama reference teaches in Figures 5 and 8, the color electroluminescent display device is an active matrix device and the motivation to combine is the same as above.

Conclusion

6. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

The following prior art are cited to further show the state of the art of composition of an OLED device.

- U.S. Patent No. 5,554,911 to Nakayama.
- U.S. Patent No. 5,780,174 to Tokito.
- U.S. Patent No. 5,909,081 to Eida.
- U.S. Patent No. 6,259,423 to Tokito.
- U.S. Patent No. 6,406,801 to Tokito.
- U.S. Patent No. 6,608,439 to Sokolik.

Application/Control Number: 10/820,570 Page 13

Art Unit: 2879

U.S. Patent No. 6,653,778 to Tomiuchi.

U.S. Patent No. 6,841,803 to Aizawa.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Dalei Dong whose telephone number is (571)272-2370. The examiner can normally be reached on 8 A.M. to 5 P.M..

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Nimeshkumar Patel can be reached on (571)272-2457. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

April 26, 2005

Joseph Williams Primary Examiner Art Unit 2879